

GREY ARGENT

SP




RECOMMENDED APPLICATIONS

FLOORS & WALLS	SHOWER FLOORS & WALLS	EXTERIOR PAVING FREEZE THAW STABLE
YES	NO	NO

TECHNICAL SPECIFICATIONS

COMPRESSIVE STRENGTH	TENSILE STRENGTH	WATER ABSORPTION	BULK DENSITY
206.9 MPa	16.12 N/mm ²	2.5%	2647 kg/m ³


STOCKED SIZES



24" x 24" x 5/8" Honed



12" x 24" x 3/8"
Honed



12" x 12" x 3/8"
Honed

SLAB SIZES



2cm & 3cm Slabs
Honed

MATERIAL

LIMESTONE

COUNTRY OF ORIGIN

SPAIN

NOTES

- OTHER SIZES OR FINISHES AVAILABLE VIA SPECIAL ORDER
- STONE IS A NATURAL PRODUCT. IT IS IMPERATIVE THAT YOU REQUEST JOB SAMPLES AND RANGE PICTURES FOR EVERY JOB
- RECOMMEND USING ARDEX N23 OR SIMILAR RAPID SETTING THINSET MORTAR WITH SELF-DRYING FORMULATION TO PREVENT WARPING, STAINING AND DISCOLORATION

RANGE

